



PRINTED CIRCUIT BOARD CAPABILITIES

ORDER TODAY.
WWW.NOISEFIGURE.COM/PCB

MANUFACTURED
IN THE USA.



ITAR REGISTERED
ISO 9001

STANDARD BOARD SPECIFICATIONS *

Specification	Value
Minimum Board Size	1in x 1in
Maximum Board Size	6in x 6in
Layer Count	1,2,4 or 6

DRILLING *

Minimum Hole Size	10mil
Minimum Annular Ring	10mil
Minimum Slot Size	25mil

FINISH PLATINGS AVAILABLE *

Electroless Nickel Immersion Gold (ENIG)
Immersion Tin
Bare Copper

FEATURES *

Minimum Trace/Space	6/6mil
Soldermask Color	Blue
Minimum Soldermask Web	4mil
Silkscreen Color	White
Minimum Silkscreen Feature Size	4mil

READY TO ORDER SUBSTRATES *

MANUFACTURER	THICKNESSES	CU THICKNESS
KINGBOARD KB-6167F	14,28,58mil	0.5oz or 1oz
ISOLA 370HR	14,28,58mil	0.5oz or 1oz
ISOLA ASTRA MT77	10 mil	0.5oz

* REACH OUT IF YOUR REQUIRED CAPABILITIES OR SUBSTRATES ARE NOT LISTED ABOVE -- MANUFACTURING@NOISEFIGURE.COM